

PUSH-BUTTON SWITCH,ILLUMINATED PUSH BUTTON & SELECTOR (ECONOMIC TYPE)








Specifications

Item	Dielectric Strength	Rated Insulation Voltage	Ambient Air Temperature	Operating Frequency (operations/h)		Service Life (operations)	
				Push-Button	Selector Switch	Mechanically	Electrically
Technical Data	2500V AC 50/60Hz for 1 Minute	600V AC	-20~50°C	1200	120	10 ⁶	5x10 ⁵

Contact Rating

Rated Current and Voltage	AC	125V	250V	600V
		10A	6A	2A
	DC	110V	220V	600V
		2A	1.1A	0.4A

Picture & Description

Type	FPB-25(30)	MPB-25(30)	LMB-25(30)	IDS-25
Pushbutton Style	Flat Pushbutton	Mushroom Head Pushbutton	Push-Locked Pushbutton	Illuminated Pushbutton Direct Type(E-10 Neon Bulb)
Pictures				
Color	R,G,B	R,G	R	R,G,Y,B,W
Type	ITS-25(30)	SKOS-25(30)	LKOS-25(30)	
Pushbutton Style	Illuminated Pushbutton With Transformer (AC 110,220,380,440V)	Knob Operated Selector Switch, 2 Position and 3 Position	Lever Operated Selector Switch, 2 Position and 3 Position	
Picture				
Color	R,G,Y,B,W	R,G,B	R,G,B	
Contact Configuration	10=1NO,01=1NC,11=1NC, 22=2NO+2NC			

Dimensions

Unit: mm

Type	Dimensions (mm)			
	D	d	L1	L2
FPB-25(30)	21(24.5)	30(34)	16(18.5)	40/48
MPB-25(30)	40	30	31	40/48
LMB-25	40	30	35	42/50
IDS-25	19	30	33	46/55
ITS-25	19	30	33	45/55
SKOS-25(30)	21	30	30	45/51
LKOS-25(30)	21	30	33	43/51

