









PB SERIES PUSHBUTTON





Specifications

Item	Dielectric Strength	Rated Insulation Voltage	Rated Current and Voltage	Ambient Air Temperature °C	Operating Frequency (operations/h)	Service Life (operations)	
						Mechanically	Electrically
Technical Data	2500V AC 50/60Hz for 1 Minute	600V AC	AC 250V, 3A	-25~40°C	1200	10 ⁶	5x10 ⁵

Dimensions

Unit: mm

Type	Picture	Dimensions (mm)	Mounting Hole	Contact Configuration
PB-XA			φ 22 φ 25	10=1NO 01=1NC 11=1NO+1NC
PB-XA-A			φ 22 φ 25	01=1NC 10=1NC 11=1NO+1NC
PB-16			φ 16	01=1NC
PB-XB (S)			φ 22 φ 25	Pilot light

PICTURE				
DESCRIPTIONS	22mm, 25mm Pushbutton with neon lamp BA9S AC 110V, 220V	22mm, 25mm Pushbutton with neon lamp BA9S AC 110V, 220V	22mm, 25mm Pushbutton with neon lamp BA9S AC 110V, 220V	30mm Pushbutton with neon lamp BA9S AC 110V, 220V
Type	APBB - 22 & 25N	AS - 22 & 25N	AB - 22 & 25N	PPBB - 30N
Rated Current and Voltage	10A 600VAC	10A 600VAC	10A 600VAC	10A 600VAC