

Latching Limit Switch with Remote Reset SSD4 SERIES (3-CONDUIT ENTRIES)

Introduction

SSD4 latching limit switch with remote reset is designed for use for applications, where an intentional reset of the switch is required. The switch can be remotely reset without being physically near it.

Applications

- overspeed governor, particularly suitable for machine room less lifts.
- Wind generators, or similar applications with service areas difficult to access

Features

- Glass fiber reinforced plastic body
- Glass fiber reinforced plastic body
- Conform to EN 60947-5-1, IEC 60947-5-1, UL508, ASME A17.1/5, EN 81-1, EN 81-2 Standards
- Reset with electric pulse 24VDC, 48VDC 120VAC or 240VAC options
- Galvanically separated contacts
- Prewired with 3 possible cable entry positions
- Positive Opening of NC contacts
- Conform to EN 50047 standard



Specifications:

Operating Speed	0.05mm-0.5m/sec
Rated Current/Voltage	10A/600V AC (EN60947-5-1)
	AC15 A600 / DC13 Q300
Service Life	Mechanically 50,000 (operations)
Operating Temperature	-25~+50°C (-13~122°F) with no icing
Actuating force	6 N (+/- 2 N)
Actuating Distance	< 0.5mm
Contact Opening	2 x 2 mm
Degree of Protection	IP67

Solenoid:

Rated voltage (Ue):	24 VDC (+/- 10%)
	48 VDC (+/- 10%)
	120 VAC (+/- 10%)
	240 VAC (+/- 10%)
Rated current (Ie):	3 A (24 VDC)
	1.5 A (48 VDC)
	0.8A (120VAC)
	0.5 A (230 V)
Solenoid duty cycle:	3% ED
Power supply time	Power supply time: min. 0.2s, max 0.5s
	Time without power supply: min. 30s
Max operating frequency:	100 operations cycles/hour

Selection Guide:

SSD41 11	-	SL6	-	D	-	120	-	L	-	2
Head Styles See drawing below for commonly used head style. See SND4 for complete head style list		Contact Block SL: 1NO/1NC Contact SL0: 1NC Contact SL2: 2NC Contact SL3: 2NO Contact SL4: 3NC Contact SL5: 3NO Contact SL6: 2NC/1NO Contact		Conduits D: M16		Solenoid voltage rating — 24: 24VDC — 48: 48VDC — 120: 110-125VAC — 240: 220-240VAC		Cable Exit — L: Cable Exit Left — M: Cable Exit Bottom — R: Cable Exit Left		Cable Length

