

FS-72 Series Medical Foot Switches

Features

- Robust glass fiber reinforced plastics housing
- Each pedal rocks left and right operating on the teeter-totter principle: Pressure on one side opens or closes line and release of returns the switch back to normal off position (Both sides are independent)
- Available in IP20 and IPX8 version

Specifications

Operating Frequency	60 ops/min
Insulation Resistance	>100MΩ@500V DC
Contact Resistance	<25mΩ
Rated Current/Voltage	10A/15A 1/2HP 250VAC
Dielectric Strength	1000VAC for 1 min between current carrying parts 2500VAC for 1 min between non-current carrying parts
Service Life	Mechanically 1 x 10 ⁶ (operations) Electrically 5 x 10 ⁵ (operations)
Operating Temperature	-30~+80°C (-22~176°F)
Degree of Protection	IP20/NEMA 1 (or IP68/NEMA 6,6P)

Selection Guide:

FS-72	-	10	-	W	-	BH	-	_____
		Electrical Rating		IP Rating		Options		Additional Suffix for Wiring
		10: 10A/250VAC		Blank: IP20		B: With pushbutton		
		15: 15A/250VAC		W: IPX8		H: With handler		
						K: Gold plated contact		

* Offer custom cable and connector according to customer requirements.

Dimensions:

FS-72-10 (not wired, IP20)
 FS-72-10-W (not wired, IP68)
 FS-72-10-W-BH (not wired, IP68 with pushbutton and handle)

