GENERAL-PURPOSE MICRO SWITCHES S19 SERIES

Features

- 5 current ratings
- Choice of actuator styles
- 3 terminal types (optional screw terminals available — consult factory)
- 3 contact arrangements
- Long-life coil spring mechanism
- High-temperature 150°C and 200°C available on select models (consult factory)

Definitions of Operating Characteristics

OF	Operating Force	PT	Pretravel
RF	Releasing Force	MD	Movement Differential
OT	Overtravel	OP	Operating Position
TT	Total Travel		

Specifications

Electrical

Electrical Rating:	15A,125/250VAC;3/4HP,125VAC 1-1/2HP,250VAC
Temperature Rating:	105°C Std. (150°C and 200°C optional)
Flammability Rating:	UL94-V0

Materials

Case:	General Purpose Phenolic
Actuating Button:	Thermoplastic Nylon
Common Terminals:	Brass
NO and NC Terminals:	Brass
Moving Blade:	Brass
Spring:	Stainless Steel
Auxiliary Actuators:	Cold-Rolled Steel (Nickel-Plated)
Roller:	Sintered Stainless Steel
Contacts:	Silver-Cadmium Oxide

Dimensions Unit: mm



S-19E

Operating Characteristics

OF(Max):	850g	OT(Min):	2.03mm(0.080inch)
PT(Max):	1.27mm(0.050inch)	MD(Max):	0.38mm(0.015inch)
		OP:	7.24±0.76mm(0.285± 0.030inch)



S-19H

Operating Characteristics

OF(Max):	205g	OT(Min):	4.75mm(0.187inch)
PT(Max):	6.99mm(0.275inch)	MD(Max):	2.36mm(0.093inch)
		OP:	7.92±1.57mm(0.312± 0.062inch)



S-19J

Operating Characteristics

OF(Max):	850g	OT(Min):	2.03mm(0.080inch)
PT(Max):	1.27mm(0.050inch)	MD(Max):	0.38mm(0.015inch)
		OP:	17.02±0.76mm(0.670± 0.030inch)



S-19K

Operating Characteristics

OF(Max):	212g	OT(Min):	4.75mm(0.187inch)
PT(Max):	6.35mm(0.250inch)	MD(Max):	2.36mm(0.093inch)
		OP:	18.24±1.57mm(0.718± 0.062inch)



S-19M

Operating Characteristics

OF(Max):	850g	OT(Min):	5.54mm(0.218inch)
PT(Max):	1.27mm(0.050inch)	MD(Max):	0.38mm(0.015inch)
		OP:	20.62±0.76mm(0.812± 0.030inch)

Note #1:
2NO OR 2NC is avaliable as request, please add"1" or"2" after the model
Example: S-19E1: 2NO
S-19E2: 2NC

Note #2:
With respect to operating sequence,pole 1 or 2 may operate first(virtually same time). If pole 1 or 2 must always operate in a particular sequence please contact us.

http://www.suns-usa.com